

Version	Modification content	Reviser	Date
A2	Revised table, added symbols ☆ of characteristics	Emily Hu	2019-3-30

Specification

Product name: Expandable sleeving

Material: PET+PA66

Working temperature: -40℃~+150℃

Melting point: 240±10℃

Low temperature resistance: No signs of embrittlement and degradation after test at -40℃ for 4h per GMW14327

☆ Heat aging resistance: No signs of embrittlement and degradation after test at 150℃ for 504h per GMW14327

Flammability: Combustion rate < 100mm/min per FMV SS302

☆ Abrasion resistance: Conform to GMW 14327 class 6 (30000~99999 times) per ISO6722-1




Color: Black

Application: Widely used in tidying and wearing protection in automotive wiring harness, rubber and plastic tubes.

Cutting tools: Hot knife, scissors

Certificate: RoHS

Part no.	Flat width (W)		Expanded range		Packaging (m/roll)
	Inch	mm	Min.(I)	Max.(O)	
010	3/8"	10	7	15	350
012	1/2"	12	8	17	300
016	5/8"	16	10	23	250
019	3/4"	19	13	28	200
022	7/8"	22	15	32	200
026	1"	26	18	35	150
038	1-1/2"	38	30	50	100
045	1-3/4"	45	35	60	100

Manufacturer	JDDTECH® SHENZHEN JDD TECH NEW MATERIAL CO., LTD ADD: Building 2, E Zone, Minzhu Western Industrial Area, Shajing Town, Baoan District, Shenzhen City, Guangdong Province, China Tel: 0755-33666001 Fax: 0755-33807127		
Specification No.	JDDKH19-0133	Unit	mm
Product code	Auto FR1130	Version	A2
REV.0		Special characteristics	☆ Represent key special characteristics
Prepared	Jinyuan Pan	Date	2019-3-30
Checked		Date	2019-3-30
Approved		Date	2019-3-30