

Polyester expandable sleeving




JDD-FR Polyester expandable sleeving is flame-retardant and halogen-free. It offers durable abrasion resistance in a wide range of industrial applications. The open weave construction allows an easy installation on a bundle of hoses and cables, even if some with bulky or large connectors. The Totally expanded sleeving can reach at least 1.5 times the initial dimension.

Application



Drawing



It's used for covering cables, wire harnesses, tubes, industrial hoses where is required an additional protection.

Datasheet

Part No.	Nominal size (W)		Expanded range		Packing (L) Standard spool(m)
	Inch	mm	Min.(I)	Max.(O)	
FR-003	1/8"	3	1	6	1000
FR-006	1/4"	6	3	9	500
FR-008	5/16"	8	5	16	350
FR-010	3/8"	10	7	19	350
FR-012	1/2"	12	8	24	350
FR-016	5/8"	16	10	27	250
FR-019	3/4"	19	14	30	200
FR-025	1"	25	18	35	200
FR-032	1-1/4"	32	20	50	150
FR-038	1-1/2"	38	30	60	100
FR-045	1-3/4"	45	35	75	100
FR-050	2"	50	40	80	100
FR-064	2-1/2"	64	45	105	100
FR-076	3"	76	64	120	100

Unit: mm

Technical data

Material	Polyester
Operating range	-50°C - +150°C
Melt point	240±10°C
Flammability	VW-1
Standard color	Black, Grey
Certificate	UL, RoHS, REACH, Halogen Free
Cutting tool	Hot knife



Notes:

- Nominal size indicates the flat width.
- The part No. will be followed with BK, GR and so on to indicate the color of sleeving.
- This sleeving has expandable character, the following sizes are covered by the nearest:
16mm=15mm, 19mm =20mm , 32mm =30mm , 38mm=40mm, 51mm=50mm.
- Special packing, sizes, and colors can be supplied upon request.
- All the numerical data are average or typical values, not including customized sizes.