

Zipper braided wrap



1.Technical data


Material:Polyester Operating range:-40 °C ~+125 °C Melt point:240±10 °C Flammability:UL94 V2 Color:Black Certificate:RoHS

2.Product Introduction

JDD-ZW Zipper braided wrap could be installing on the cable harness very easily just like closing your coat with the zipper. It can offer an additional protection against flame and abrasion. It allows us to install or uninstall wires and cables very quickly and easily due to its special structure.

Most commonly be used on wires, wire bundles and harnesses, cable assemblies, flat ribboncable, tubing and hoses to provide a tough, durable protection in home, office, railway.

3.Application



4.Datasheet

| Part No. | Nominal size | Max. bundle dia. | Packing |
|----------|--------------|------------------|------------|
| ZW-12 | 12 | 8 | On request |
| ZW-20 | 20 | 15 | On request |
| ZW-30 | 30 | 20 | On request |
| ZW-50 | 50 | 35 | On request |
| ZW-64 | 64 | 45 | On request |

Notes

Notes: 1.Nominal size indicates the flat width , I.D. indicates round inner diameter. 2.The part No. will be followed by BK, WH, GR and so on to indicate the color . 3.Special packages, sizes and colors can be supplied upon request. 4.All numerical data are average value, not including customized sizes.