



RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.5 ± 0.3 µIn/Out
Ink Thickness	4.0 ± 0.2 µ
Total Thickness	8.5 ± 0.5 µ
Transfer Temperature	188°F / 87°C

PRODUCT FEATURES

- BS5609
- FDA Indirect Food Contact
- REACHCompliant
- RoHSCompliant
- Halogen-free

RECOMMENDED SUBSTRATES

TAG / PAPER

- Coated Tag
- Uncoated Tag
- Coated Face Sheets
- Uncoated Face Sheets
- Gloss Sheets

SYNTHETICS

- Polypropylene
- Polyethylene
- Polystyrene
- Polyolefin
- Vinyl (Topcoat)
- Polyesters (Matte)

SPECIALTY MATERIALS

- Tyvek®
- Tyvek Brillion®
- Valeron®

RECOMMENDED APPLICATIONS

AUTOMOTIVE



COMPLIANCE



ELECTRONICS



FOOD & BEVERAGE



HEALTH & BEAUTY



INVENTORY & LOGISTICS



OUTDOOR



PHARMACEUTICAL



RETAIL



UL / cUL LABELING REFERENCES

3M:	PGJ12.MH16411, PGJ12.MH18072
Avery Dennison:	PGJ18.MH17205, PGJ12.MH20580
FLEXcon:	PGJ12.MH16635
Mactac:	PGJ12.MH26726