

RB- Wax Resin

General Description:

3.5-mil flexible frosty clear vinyl is an intermediate vinyl for general screen printing. This film is designed for multiple color labels and decals, bumper strips and other identification pieces.

Have moderate conformable characteristics

Features:

3.5 mil frosty clear flexible vinyls 07 adhesive
78#bleached Kraft liner

Face Material:

frosty clear

Adhesive:

07 medium tack permanent acrylic

Liner:

78#bleached clay-coated Kraft

Average Adhesion Values:

15 min.

24 hr.

Pstc-1, 180°c peel @ 12"/min., 50 oz.

64 oz.(73°f, on Stainless Steel)

Service Temperature Range:

-40°f to +180°f

Shelf Life (@ 73°f , 50% RH):

2 years

Minimum Application

50°f

Temperature:

Outdoor Durability:

2 years

UL approved Recommended TT Ribbons:

P/N: 712-tuv-wzy-z

Others

P/N: RBWR-tuc-wzy-z

Recommended TT Ribbons:

Certifications:

UL-MH45621- Component Printing Materials

Chemical Resistance:

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	N/A
Ammonium hydroxide (10 min) %10	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect

Agency Approvals: UL File No. MH 45621 Group PGJ12 (Based on labels-ribbons system)