




(index.html)

Heat Shrinking Tube and Sleeves, Heat-Shrinkable Tubing

Custom Polyolefin Heat Shrink Tubing, Silicone Rubber Heat Shrink Tubing Manufacturer





[Home \(/\)](#) / [Products \(products.html\)](#)

[/ Heat Shrink Tubing \(1-heat-shrink-tubing.html\)](#)

[/ Special Purpose Heat Shrink Tubing \(1-4-special-purpose-heat-shrink-tubing.html\)](#)

[/ Silicone Rubber Heat Shrink Tubing](#)

[Single Wall Heat Shrink Tubing \(1-1-single-wall-heat-shrink-tubing.html\)](#)

[Dual Wall Heat Shrink Tubing \(1-2-dual-wall-heat-shrink-tubing.html\)](#)

[Heavy Duty Heat Shrink Tubing \(1-3-heavy-duty-heat-shrink-tubing.html\)](#)

[Special Purpose Heat Shrink Tubing \(1-4-special-purpose-heat-shrink-tubing.html\)](#)

[Printable Heat Shrink Tubing \(1-5-printable-heat-shrink-tubing.html\)](#)

[Heat Shrink Busbar Tubing \(1-6-heat-shrink-busbar-tubing.html\)](#)

[Cold Shrink Tubing \(2-cold-shrink-tubing.html\)](#)

[Non Heat Shrink Tubing and Sleeve \(3-non-heat-shrink-tubing-and-sleeve.html\)](#)

[Cable Accessories \(4-cable-accessories.html\)](#)

[Heat Shrink Cable Accessories \(4-1-heat-shrink-cable-accessories.html\)](#)

[Cold Shrink Cable Accessories \(4-2-cold-shrink-cable-accessories.html\)](#)

[Wraparound Heat Shrink Cable Repair Sleeve \(4-3-wraparound-heat-shrink-cable-repair-sleeve.html\)](#)

Silicone Rubber Heat Shrink Tubing

Model: CB-SRT(S)

Application

The silicone rubber heat shrink tubing is designed to provide insulation and shielding for electronic accessories that have special requirements. Usually, this heat shrink tubing is used for electrical equipment, light fixtures and medical instruments. In addition, this silicone rubber tubing has a high temperature resistance of up to 200°C.




(products/1-4-10-silicone-rubber-heat-shrink-tubing_01.jpg)

Standard: AS23053/10

Size

Size	OD as supplied (mm)	Before recovery (mm)		After recovery (mm)		Packing form	
		Inside diameter (mm)	Wall thickness (mm)	Inside diameter (mm)	Wall thickness (mm)	A	B
φ1.5	1.1~1.4	1.7±0.2	0.5±0.1	0.8±0.1	1.0±0.2	2.5×1m/pack	5×5m/pack
φ3.0	1.8~2.5	3.2±0.2	0.5±0.1	1.6±0.1	1.0±0.2	20×1m/pack	4×5m/pack
φ4.0	2.3~4.0	4.5±0.3	0.5±0.1	2.2±0.1	1.0±0.2		
φ5.0	2.8~5.0	5.6±0.3	0.5±0.1	2.9±0.2	1.0±0.2		
φ6.0	3.2~6.0	6.6±0.3	0.5±0.1	3.3±0.2	1.0±0.2	10×1m/pack	2×5m/pack
φ8.0	4.5~7.0	8.6±0.4	0.5±0.1	4.3±0.2	1.0±0.2		
φ12	6.0~10	12±1.0	0.75±0.1	6.0±0.2	1.5±0.2		
φ17	9~15	17±1.0	0.75±0.1	9.0±0.2	1.5±0.2	5×1m/pack	1×5m/pack
φ20	12~21	23±1.0	1.0±0.1	12±0.4	2.0±0.3		
φ25	15~23	25±1.0	1.0±0.1	14±0.4	2.0±0.3		
φ30	18~28	31±1.0	1.0±0.1	16±0.5	2.0±0.3	5×1m/pack	1×5m/pack
φ45	25~42	45±1.0	1.5±0.1	23±1.0	3.0±0.3		
φ55	33~50	55±1.0	1.5±0.1	29±1.0	3.0±0.3		
φ65	40~60	66±2.0	1.5±0.1	35±1.0	3.0±0.3		



Contact Us
([contact.html](#))

Remarks: Special sizes and customization services are available upon request.

CYG Electronics Ltd.
Industrial
([index.html](#)) Min Industrial
Park 2#, Dalang Town,
Dongguan City,
Guangdong Province

Contact Person:
Bryant Chen (Mr.)
Tel.: +86-769-89388009
(tel:+86-769-89388009)
Fax: +86-769-89388027
E-mail:
sales@cyelectr.com
(mailto:sales@cyelectr.com)

Tags

silicone rubber tubing
heat shrink tubing

Specifications

Items	Flame Retardant Type	Normal Type
Expansion Strength MPa(Kg/cm ²)	6.9	6.9
Elongation%	400	400
Tear Strength kN/m(kg f/cm)	24.5(25)	24.5(25)
Volume Resistance Ω·m(Ω·cm)	2×10 ¹² (2×10 ¹⁴)	2×10 ¹² (2×10 ¹⁴)
Dielectric Strength kV/mm	25	25
Dielectric Constant (ε)50Hz	3.2	3.2
Dielectric Loss Angle Tangent 50Hz	0.001	0.001
Flame Retardancy UL-224	VW-1	—
Temperature Range °C	-50~+200	-50~+200
Axial Shrinkage%	About50	About50
Shrinkable Temperature°C	> 90	> 90

Heat Shrink Tubing



(1-4-2-heat-shrink-polyolefin-tubing.html)

PVDF Heat Shrink Tubing for 175 °C (1-4-2-heat-shrink-polyolefin-tubing.html)



(1-4-3-heat-shrink-fluoropolymer-tubing.html)

Heat Shrink Fluoropolymer Tubing (1-4-3-heat-shrink-fluoropolymer-tubing.html)



(1-4-4-ptfe-heat-shrink-tubing.html)

PTFE Heat Shrink Tubing (1-4-4-ptfe-heat-shrink-tubing.html)



(1-4-5-heat-shrink-fiber-braided-sleeving.html)

Heat Shrink Fiber Braided Sleeving (1-4-5-heat-shrink-fiber-braided-sleeving.html)



(1-4-6-diesel-resistant-heat-shrink-tubing.html)

Diesel Resistant Heat Shrink Tubing (1-4-6-diesel-resistant-heat-shrink-tubing.html)



(1-4-7-polyolefin-heat-shrink-film.html)

PET Heat Shrink Film (1-4-7-



(1-4-8-fep-heat-shrink-tubing.html)

FEP Heat Shrink Tubing (1-4-8-fep-



(1-4-9-pfa-heat-shrink-tubing.html)

PFA Heat Shrink Tubing (1-4-9-pfa-



(1-4-10-silicone-rubber-heat-shrink-tubing.html)

Silicone Rubber Heat



(1-4-11-heat-shrink-molded-shapes.html)

Heat Shrink Molded Shapes (1-4-



[polyolefin-heat-shrink-film.html](#))

[heat-shrink-tubing.html](#))

[heat-shrink-tubing.html](#))

[Shrink Tubing \(1-4-10-silicone-rubber-heat-shrink-tubing.html\)](#)

[11-heat-shrink-molded-shapes.html](#))



[\(index.html\)](#)

Inquiry

E-mail*

Name

Phone

Message*

Send

- [Home \(index.html\)](#)
- [About Us \(company.html\)](#)
- [Products \(products.html\)](#)
- [Guide \(guide.html\)](#)
- [Custom Service \(custom-service.html\)](#)
- [Factory Tour \(factory-tour.html\)](#)
- [Video \(video.html\)](#)
- [Contact Us \(contact.html\)](#)

[LEGAL \(http://www.etwinternational.com/legal-profile.html\)](#) [SITEMAP \(http://cyshrinktubing.com/sitemap.html\)](#)

Supported by ETW International Inc. USA (<https://www.etwinternational.com/>)

